

ZX Series Fixed Velocity Thickness Gauges



Highlights:

- ▶ Easy to operate.
- ▶ Pulse-echo measurement.
- ▶ Dual element transducers (1-10MHz options).
- ▶ 120MHz FPGA timing.
- ▶ 150 volt square wave pulser.
- ▶ Low temperature custom LCD display (-22 F / -30C).
- ▶ Adjustable material velocity.
- ▶ Selectable material list (ZX-2 only).
- ▶ IP65 protection rating.
- ▶ 5 year limited warranty.

ZX-1 & ZX-2 THICKNESS GAUGES

The **ZX-1 & 2** are basic fixed velocity gauges that require no special training to operate. Calibration is done by simply scrolling to a known material velocity, or selecting a common material from a list of material types in the **ZX-2**. The gauges were designed and built to withstand the roughest industry conditions, are affordable, and backed by a 5 year limited warranty. If you're looking for a quality instrument to reliably meet or exceed your application expectations, look no further.

SPECIFICATIONS

Physical

Weight:

11 ounces (with batteries).

Size:

Width (2.5 in / 63.5 mm)
Height (5.17 in / 131.3 mm)
Depth (1.24 in / 31.5 mm)

Operating Temperature:

-22 to 167F (-30 to 75C).

Case:

Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed).

Keypad

Sealed membrane that is resistant to both water and petroleum products.

Seven or eight tactile-feedback keys.

Transducer

Dual-element (transmit and receive).

1 to 10 MHz frequency range.

Locking quick disconnect LEMO connectors.

4 foot cable.

Custom transducers available for special applications.

Power Source

Two 1.5V alkaline, 1.2V NiCad, or 1.5V Lithium AA cells.

Typically operates for 45 hours on alkaline and 23 hours on NiCad.

Low battery indicator on display. Unit turns off automatically when battery is too low to operate reliably.

Display

Multi-function 7 segment 4.5 digit liquid crystal display with 0.500 in digit height. Two 0.125 in 14 segment fields for labels and values, and one 7 segment field for labels and values. Additional icons to indicate features and modes.

Backlight is selectable on/off/auto, and selectable brightness (Lo, Med, Hi) options.

Bar graph indicates stability of reading.

Certification

Factory calibration traceable to NIST & MIL-STD-45662A.

Warranty

5 year limited.

Measuring

Range:

Measures from 0.025 to 36.00 inches (0.63 to 1219.2 millimeters). Range dependent on material and transducer type.

Units:

English & Metric

Resolution:

0.001 inches (0.01 millimeters)

Velocity Range:

0.0120 to .7300 in/ μ s (305 to 18,542 m/sec)

PRF: 200Hz

Display Update Rate: 10Hz

Velocity Settings:

ZX-1: Adjustable on keypad.

ZX-2: Adjustable on keypad and selectable from 8 factory presets and 2 programmable custom velocity options.

Velocity Chart	in. / mm
1. Steel 4340	.2330 / 5918
2. Stainless 303	.2230 / 5664
3. Aluminum 2024	.2510 / 6375
4. Cast Iron	.1800 / 4572
5. Plexiglass	.1060 / 2692
6. PVC	.0940 / 2388
7. Polystyrene	.0920 / 2337
8. Polyurethane	.0700 / 1778
9. Custom	
10. Custom	



MADE IN THE USA

Specifications subject to change without notice. (E & O.E.)



Advanced NDT Limited
Unit 4 Elgar Business Centre
Moseley Road
Hallow, Worcester
WR2 6NJ, England
Tel: 01905 371460

Advanced NDT

Web: www.advanced-ndt.co.uk
Email: sales@advanced-ndt.co.uk



DAKOTA ULTRASONICS

1500 Green Hills Road, #107

Scotts Valley, CA 95066

Ph: (831) 431-9722

Fax: (831) 431-9723

Website: www.dakotaultrasonics.com

Email: info@dakotaultrasonics.com